

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878 Issue date: 3/25/2011 Revision date: 1/2/2023 Supersedes version of: 8/1/2021 Version: 5.00

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Name : Anti-corrosion Epoxy Primer

Trade name : UNDER 395 Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : The product is intended for professional use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

NOVOL Sp. z o.o. Żabikowska 7/9 62-052 KOMORNIKI

Poland

T 0048618109800 - F 0048618109809

www.novol.com

E-mail address of competent person responsible for the SDS: dokumentacja@novol.com

1.4. Emergency telephone number

Emergency number : 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis H336
Hazardous to the aquatic environment – Chronic Hazard, Category 3
H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :





GHS02 GHS07

Signal word (CLP) : Danger

Contains : dimethyl ether; acetone

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H315 - Causes skin irritation. H319 - Causes serious eye irritation.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

H336 - May cause drowsiness or dizziness.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use. P260 - Do not breathe vapours, spray. P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, eye protection, face protection.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122

۰F

EUH-statements : EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
dimethyl ether substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit (Note U)	CAS-No.: 115-10-6 EC-No.: 204-065-8 EC Index-No.: 603-019-00-8 REACH-no: 01-2119472128- 37	25 – 50	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
acetone substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-	25 – 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
xylene substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit (Note C)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216- 32	< 10	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
propan-2-ol; isopropyl alcohol; isopropanol substance with national workplace exposure limit(s) (GB)	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119457558- 25	< 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] substance with national workplace exposure limit(s) (GB) (Note V)(Note W)(Note 10)	CAS-No.: 13463-67-7 EC-No.: 236-675-5 EC Index-No.: 022-006-00-2 REACH-no: 01-2119489379- 17	< 5	Carc. 2, H351

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-methylpropan-1-ol; iso-butanol substance with national workplace exposure limit(s) (GB)	CAS-No.: 78-83-1 EC-No.: 201-148-0 EC Index-No.: 603-108-00-1 REACH-no: 01-2119484609- 23	< 2.5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336 STOT SE 3, H335
zinc oxide	CAS-No.: 1314-13-2 EC-No.: 215-222-5 EC Index-No.: 030-013-00-7 REACH-no: 01-2119463881- 32	< 1	Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Note 10 - The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter \leq 10 μ m.

Note C - Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note U - When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:. Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.). Aerosols shall not be classified as gases under pressure (See Annex I. Part 2. Section 2.3.2.1, Note 2).

Note V - If the substance is to be placed on the market as fibres (with diameter $< 3 \mu m$, length $> 5 \mu m$ and aspect ratio $\ge 3:1$) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied.

Note W - It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation.

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : General information. Refer to section 11.

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable

for breathing.

First-aid measures after skin contact : After contact with skin, take off immediately all contaminated clothing, and wash

immediately with plenty of water and soap. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. If skin irritation continues, consult a doctor.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. Call a physician immediately. In case of contact with eyes, rinse

immediately with plenty of water and seek medical advice.

First-aid measures after ingestion : If swallowed: rinse mouth. Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Vapours may cause drowsiness and dizziness.

Symptoms/effects after skin contact : Prolonged or repeated contact may cause skin to become dry.

Symptoms/effects after eye contact : May cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry chemical, CO2, alcohol-resistant foam or waterspray.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Carbon monoxide. Other toxic gases.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Remove ignition sources. Ensure that there is a suitable ventilation system. Avoid any direct

or indirect contact with ingredients released. Avoid contact with skin and eyes. Use personal

protective equipment as required. See Section 8.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. See Section 8.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains. Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

6.3. Methods and material for containment and cleaning up

For containment : Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Mechanically

recover the product.

6.4. Reference to other sections

Disposal considerations. See Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Pressurized container. Do not spray on an open flame or other ignition source. Ensure good

ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Wear

personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be

allowed out of the workplace. Do not eat, drink or smoke when using this product. Always

wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Pressurized container. Protect from sunlight and do not expose to temperatures exceeding

50°C. Do not pierce or burn, even after use. Keep away from ignition sources. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Keep out of reach of

children.

7.3. Specific end use(s)

No additional information available

1/2/2023 (Revision date) GB - en 4/16

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

dimethyl ether (115-10-6)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Dimethylether	
IOEL TWA [ppm]	1000 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
United Kingdom - Occupational Exposure Limits		
Local name	Dimethyl ether	
WEL TWA (OEL TWA) [1]	766 mg/m³	
WEL TWA (OEL TWA) [2]	400 ppm	
WEL STEL (OEL STEL)	958 mg/m³	
WEL STEL (OEL STEL) [ppm]	500 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
acetone (67-64-1)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Acetone	
IOEL TWA [ppm]	500 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
United Kingdom - Occupational Exposure Limits		
Local name	Acetone	
WEL TWA (OEL TWA) [1]	1210 mg/m³	
WEL TWA (OEL TWA) [2]	500 ppm	
WEL STEL (OEL STEL)	3620 mg/m³	
WEL STEL (OEL STEL) [ppm]	1500 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
xylene (1330-20-7)		
EU - Indicative Occupational Exposure Limit (IOE	L)	
Local name	Xylene, mixed isomers, pure	
IOEL TWA [ppm]	50 ppm	
IOEL STEL	442 mg/m³	
IOEL STEL [ppm]	100 ppm	
Remark	Skin	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
United Kingdom - Occupational Exposure Limits		
Local name	Xylene	
WEL TWA (OEL TWA) [1]	220 mg/m³ o-,m-,p- or mixed isomers	
WEL TWA (OEL TWA) [2]	50 ppm o-,m-,p- or mixed isomers	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

WEL STEL (OEL STEL) [ppm] Remark Sk (Can be at are concerns) Regulatory reference EH40/2005 (F United Kingdom - Biological limit values Local name Xylene, o-, m- BMGV 650 mmol/molime: Post shir	m-,p- or mixed isomers psorbed through the skin. The assigned substances are those for which there that dermal absorption will lead to systemic toxicity) Fourth edition, 2020). HSE To or mixed isomers I Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling fit Fourth edition, 2020). HSE	
WEL STEL (OEL STEL) [ppm] 100 ppm o-,m Remark Sk (Can be at are concerns Regulatory reference EH40/2005 (F United Kingdom - Biological limit values Local name Xylene, o-, m- BMGV 650 mmol/mo time: Post shir Regulatory reference EH40/2005 (F propan-2-ol; isopropyl alcohol; isopropanol (67-63-0) United Kingdom - Occupational Exposure Limits Local name Propan-2-ol WEL TWA (OEL TWA) [1] 999 mg/m³ WEL TWA (OEL TWA) [2] 400 ppm WEL STEL (OEL STEL) 1250 mg/m³	p-,p- or mixed isomers psorbed through the skin. The assigned substances are those for which there that dermal absorption will lead to systemic toxicity) Fourth edition, 2020). HSE -, p- or mixed isomers I Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling ft	
Remark Sk (Can be at are concerns) Regulatory reference EH40/2005 (F United Kingdom - Biological limit values Local name Xylene, o-, m- 650 mmol/mo time: Post shi Regulatory reference EH40/2005 (F propan-2-ol; isopropyl alcohol; isopropanol (67-63-0) United Kingdom - Occupational Exposure Limits Local name Propan-2-ol WEL TWA (OEL TWA) [1] WEL TWA (OEL TWA) [2] WEL STEL (OEL STEL) 1250 mg/m³	psorbed through the skin. The assigned substances are those for which there that dermal absorption will lead to systemic toxicity) Fourth edition, 2020). HSE , p- or mixed isomers I Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling ft	
are concerns Regulatory reference EH40/2005 (F United Kingdom - Biological limit values Local name Xylene, o-, m- BMGV 650 mmol/mo time: Post shir Regulatory reference EH40/2005 (F propan-2-ol; isopropyl alcohol; isopropanol (67-63-0) United Kingdom - Occupational Exposure Limits Local name Propan-2-ol WEL TWA (OEL TWA) [1] 999 mg/m³ WEL TWA (OEL TWA) [2] 400 ppm WEL STEL (OEL STEL) 1250 mg/m³	that dermal absorption will lead to systemic toxicity) Fourth edition, 2020). HSE -, p- or mixed isomers I Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling ft	
United Kingdom - Biological limit values Local name Xylene, o-, m- BMGV 650 mmol/mo time: Post shir Regulatory reference EH40/2005 (F propan-2-ol; isopropyl alcohol; isopropanol (67-63-0) United Kingdom - Occupational Exposure Limits Local name Propan-2-ol WEL TWA (OEL TWA) [1] 999 mg/m³ WEL TWA (OEL TWA) [2] 400 ppm WEL STEL (OEL STEL) 1250 mg/m³	-, p- or mixed isomers I Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling ft	
Local name Kylene, o-, m- BMGV 650 mmol/mo time: Post shi Regulatory reference EH40/2005 (F propan-2-ol; isopropyl alcohol; isopropanol (67-63-0) United Kingdom - Occupational Exposure Limits Local name Propan-2-ol WEL TWA (OEL TWA) [1] WEL TWA (OEL TWA) [2] WEL STEL (OEL STEL) 1250 mg/m³	I Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling ft	
BMGV 650 mmol/mo time: Post shir Regulatory reference EH40/2005 (F propan-2-ol; isopropyl alcohol; isopropanol (67-63-0) United Kingdom - Occupational Exposure Limits Local name Propan-2-ol WEL TWA (OEL TWA) [1] 999 mg/m³ WEL TWA (OEL TWA) [2] 400 ppm WEL STEL (OEL STEL) 1250 mg/m³	I Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling ft	
time: Post shi Regulatory reference EH40/2005 (F propan-2-ol; isopropyl alcohol; isopropanol (67-63-0) United Kingdom - Occupational Exposure Limits Local name Propan-2-ol WEL TWA (OEL TWA) [1] 999 mg/m³ WEL TWA (OEL TWA) [2] 400 ppm WEL STEL (OEL STEL) 1250 mg/m³	ft	
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0) United Kingdom - Occupational Exposure Limits Local name Propan-2-ol WEL TWA (OEL TWA) [1] 999 mg/m³ WEL TWA (OEL TWA) [2] 400 ppm WEL STEL (OEL STEL) 1250 mg/m³	Fourth edition, 2020). HSE	
United Kingdom - Occupational Exposure Limits Local name Propan-2-ol WEL TWA (OEL TWA) [1] 999 mg/m³ WEL TWA (OEL TWA) [2] 400 ppm WEL STEL (OEL STEL) 1250 mg/m³		
Local name Propan-2-ol WEL TWA (OEL TWA) [1] 999 mg/m³ WEL TWA (OEL TWA) [2] 400 ppm WEL STEL (OEL STEL) 1250 mg/m³		
WEL TWA (OEL TWA) [1] 999 mg/m³ WEL TWA (OEL TWA) [2] 400 ppm WEL STEL (OEL STEL) 1250 mg/m³		
WEL TWA (OEL TWA) [2] 400 ppm WEL STEL (OEL STEL) 1250 mg/m³		
WEL STEL (OEL STEL) 1250 mg/m³		
WEL STEL (OEL STEL) [nnm] 500 nnm		
WEE O'LE (OEE O'LE) [pp]		
Regulatory reference EH40/2005 (F	Fourth edition, 2020). HSE	
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)		
United Kingdom - Occupational Exposure Limits		
Local name Titanium dioxi	ide	
WEL TWA (OEL TWA) [1] 4 mg/m³ respi 10 mg/m³ total		
Regulatory reference EH40/2005 (F	Fourth edition, 2020). HSE	
2-methylpropan-1-ol; iso-butanol (78-83-1)		
United Kingdom - Occupational Exposure Limits		
Local name 2-Methylpropa	an-1-ol	
WEL TWA (OEL TWA) [1] 154 mg/m ³		
WEL TWA (OEL TWA) [2] 50 ppm		
WEL STEL (OEL STEL) 231 mg/m³		
WEL STEL (OEL STEL) [ppm] 75 ppm		
Regulatory reference EH40/2005 (F		

8.1.2. Recommended monitoring procedures

Monitoring methods	
Monitoring methods	EN 482. Workplace exposure - General requirements for the performance of procedures
	for the measurement of chemical agents.

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):







8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Viton® II	6 (> 480 minutes)	0,7 mm		EN 374-3
Disposable gloves	Nitrile rubber (NBR)	2 (> 30 minutes)	0,4 mm		EN 374-3

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device	Filter type	Condition	Standard
Gas mask with filter type	Filter A1/B1		EN 14387

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : Various colours.

Appearance : Aerosol.

Odour : characteristic.

Odour threshold : Not available

Melting point : Not applicable

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

: Not available Freezing point : Not applicable Boiling point Flammability : Not applicable Explosive properties : No data available. Not available **Explosive limits** Lower explosion limit 2.6 vol % Upper explosion limit 26.2 vol % Flash point Not applicable Auto-ignition temperature : Not applicable Decomposition temperature : Not available : Not available рΗ Viscosity, kinematic : Not available Solubility : Slightly soluble. Partition coefficient n-octanol/water (Log Kow) : Not available · 4000 hPa Vapour pressure Vapour pressure at 50°C : Not available Density : 0.8 g/cm³ Relative density : Not available Relative vapour density at 20°C : Not available Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : < 90 %

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Prevent build-up of electrostatic charges (e.g, by grounding).

10.5. Incompatible materials

No contact with: strong acids, strong bases and strong oxidants.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce: Carbon monoxide. Other toxic gases.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

dimethyl ether (115-10-6)		
LC50 Inhalation - Rat	308.5 mg/l Source: International Uniform ChemicaL Information Database	
LC50 Inhalation - Rat [ppm]	164000 ppm Animal: rat, Animal sex: male, 95% CL: 142000 - 203000	
acetone (67-64-1)		
LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female	
LD50 dermal rabbit	> 7400 mg/kg Source: ECHA	
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4	
LC50 Inhalation - Rat (Vapours)	76 mg/l Source: ECHA	
xylene (1330-20-7)		
LD50 oral rat	3523 mg/kg rat	
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male	
LC50 Inhalation - Rat	27124 mg/l	
propan-2-ol; isopropyl alcohol; isopropan	ol (67-63-0)	
LD50 oral rat	5840 mg/kg Source: ECHA	
LD50 dermal rabbit	12800 mg/kg Source: ECHA	
zinc oxide (1314-13-2)		
LD50 oral rat	> 5000 mg/kg Source: ECHA	
LD50 dermal rat	> 2000 mg/kg Source: ECHA	
titanium dioxide; [in powder form containi	ing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)	
LC50 Inhalation - Rat (Dust/Mist)	> 6.82 mg/l Source: ECHA	
2-methylpropan-1-ol; iso-butanol (78-83-1))	
LD50 oral rat	2460 mg/kg Source: ECHA	
LD50 dermal rabbit	2460 mg/kg Source: ECHA	
LC50 Inhalation - Rat (Vapours)	19.6 mg/l Source: ECHA	
Skin corrosion/irritation	: Causes skin irritation.	
zinc oxide (1314-13-2)		
рН	6.95 Source: HSDB	
titanium dioxide; [in powder form containi	ing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)	
рН	7 Source: ECHA	
Serious eye damage/irritation	: Causes serious eye irritation.	
zinc oxide (1314-13-2)		
рН	6.95 Source: HSDB	
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)		
рН	7 Source: ECHA	
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)	
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)	
Carcinogenicity	: Not classified. (Based on available data, the classification criteria are not met)	
propan-2-ol; isopropyl alcohol; isopropan	ol (67-63-0)	
IARC group	3 - Not classifiable	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

titanium dioxide; [in powder form containing	1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity :	Not classified (Based on available data, the classification criteria are not met)
acetone (67-64-1)	
LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)
STOT-single exposure :	May cause drowsiness or dizziness.
acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
propan-2-ol; isopropyl alcohol; isopropanol (6	67-63-0)
STOT-single exposure	May cause drowsiness or dizziness.
2-methylpropan-1-ol; iso-butanol (78-83-1)	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
STOT-repeated exposure :	Not classified (Based on available data, the classification criteria are not met)
xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
zinc oxide (1314-13-2)	
LOAEL (dermal, rat/rabbit, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
NOAEL (oral, rat, 90 days)	31.52 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
2-methylpropan-1-ol; iso-butanol (78-83-1)	
NOAEL (oral, rat, 90 days)	> 1450 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
Aspiration hazard :	Not classified (Based on available data, the classification criteria are not met)
UNDER 395	
Vaporizer	Aerosol
propan-2-ol; isopropyl alcohol; isopropanol (6	67-63-0)
Viscosity, kinematic	2.658 mm²/s
2-methylpropan-1-ol; iso-butanol (78-83-1)	
Viscosity, kinematic	38702.757 mm²/s

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term : Not classified (Based on available (acute)

: Not classified (Based on available data, the classification criteria are not met)

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Hazardous to the aquatic environment, long-term

: Harmful to aquatic life with long lasting effects.

(chronic)

Not rapidly degradable

recording and grandeness	
dimethyl ether (115-10-6)	
LC50 - Fish [1]	> 4.1 g/l Test organisms (species): Poecilia reticulata
EC50 - Crustacea [1]	> 4.4 g/l Test organisms (species): Daphnia magna
EC50 96h - Algae [1]	154.917 mg/l Test organisms (species): other:green algae
acetone (67-64-1)	
LC50 - Fish [1]	6210 - 8120 mg/l Source: ECHA
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
xylene (1330-20-7)	
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)
LC50 - Fish [1]	10000 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	9640 mg/l Test organisms (species): Pimephales promelas
titanium dioxide; [in powder form containing	1 % or more of particles with aerodynamic diameter ≤ 10 μm] (13463-67-7)
LC50 - Fish [1]	> 100 mg/l
EC50 72h - Algae [1]	> 50 mg/l Source: ECHA
2-methylpropan-1-ol; iso-butanol (78-83-1)	
LC50 - Fish [1]	1430 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	1100 mg/l Test organisms (species): Daphnia pulex
EC50 72h - Algae [1]	593 mg/l Source: ECHA
NOEC (chronic)	20 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

dimethyl ether (115-10-6)		
Partition coefficient n-octanol/water (Log Pow)	0.1 Source: International Chemical Safety Cards	
acetone (67-64-1)		
Partition coefficient n-octanol/water (Log Pow)	-0.24 Source: ICSC	
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)		
Partition coefficient n-octanol/water (Log Pow)	0.05 Source: ICSC	
2-methylpropan-1-ol; iso-butanol (78-83-1)		
Partition coefficient n-octanol/water (Log Pow)	0.8 Source: ChemIDPlus	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

12.4. Mobility in soil

dimethyl ether (115-10-6)	
Mobility in soil	27 Source: National Library of Medicine/Hazardous Substances Data Bank

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)

Waste treatment methods

Sewage disposal recommendations

Product/Packaging disposal recommendations

Additional information

European List of Waste (LoW) code

- : Disposal must be done according to official regulations.
- Dispose of contents/container in accordance with licensed collector's sorting instructions.
- Do not discharge into drains.
- : This material and its container must be disposed of as hazardous waste. Do not dispose of with domestic waste. After cleaning, recycle or dispose of at an authorised site.
- : Flammable vapours may accumulate in the container.
- : 08 01 11* waste paint and varnish containing organic solvents or other dangerous

substances

15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA	
14.1. UN number or ID number			
UN 1950	UN 1950	UN 1950	
14.2. UN proper shipping name			
AEROSOLS	AEROSOLS	Aerosols, flammable	
Transport document description		,	
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	
14.3. Transport hazard class(es)			
2.1	2.1	2.1	
	***	*	
14.4. Packing group			
Not applicable	Not applicable	Not applicable	
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

ADR	IMDG	IATA	
No supplementary information available			

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F Limited quantities (ADR) : 1I

Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR) : MP9
Transport category (ADR) : 2
Special provisions for carriage - Packages (ADR) : V14

Tunnel restriction code (ADR) : D

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Limited quantities (IMDG) : SP277

Special packing provisions (IMDG) : PP87, L2

EmS-No. (Fire) : F-D

EmS-No. (Spillage) : S-U

Stowage category (IMDG) : None

Stowage and handling (IMDG) : SW1, SW22

Segregation (IMDG) : SG69

Air transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Name		Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see https://ec.europa.eu/home-affairs/system/files/2021-11/list_of_competent_authorities_and_national_contact_points_en.pdf

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

SDS EU format according to COMMISSION REGULATION (EU) 2020/878.

Abbreviations and acronyms:			
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways		
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road		
ATE	Acute Toxicity Estimate		
BCF	Bioconcentration factor		
BLV	Biological limit value		
BOD	Biochemical oxygen demand (BOD)		
COD	Chemical oxygen demand (COD)		
DMEL	Derived Minimal Effect level		
DNEL	Derived-No Effect Level		
EC-No.	European Community number		
EC50	Median effective concentration		
EN	European Standard		
IARC	International Agency for Research on Cancer		
IATA	International Air Transport Association		
IMDG	International Maritime Dangerous Goods		
LC50	Median lethal concentration		
LD50	Median lethal dose		
LOAEL	Lowest Observed Adverse Effect Level		
NOAEC	No-Observed Adverse Effect Concentration		
NOAEL	No-Observed Adverse Effect Level		
NOEC	No-Observed Effect Concentration		

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Abbreviations and acronyms:			
OECD	Organisation for Economic Co-operation and Development		
OEL	Occupational Exposure Limit		
PBT	Persistent Bioaccumulative Toxic		
PNEC	Predicted No-Effect Concentration		
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail		
SDS	Safety Data Sheet		
STP	Sewage treatment plant		
ThOD	Theoretical oxygen demand (ThOD)		
TLM	Median Tolerance Limit		
VOC	Volatile Organic Compounds		
CAS-No.	Chemical Abstract Service number		
N.O.S.	Not Otherwise Specified		
vPvB	Very Persistent and Very Bioaccumulative		
ED	Endocrine disrupting properties		

Data sources : ECHA (European Chemicals Agency).

Training advice : Handle in accordance with good industrial hygiene and safety procedures.

Full text of H- and EUH-statements:			
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4		
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4		
Aerosol 1	Aerosol, Category 1		
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1		
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1		
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3		
Carc. 2	Carcinogenicity, Category 2		
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.		
Eye Dam. 1	Serious eye damage/eye irritation, Category 1		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2		
Flam. Gas 1A	Flammable gases, Category 1A		
Flam. Liq. 2	Flammable liquids, Category 2		
Flam. Liq. 3	Flammable liquids, Category 3		
H220	Extremely flammable gas.		
H222	Extremely flammable aerosol.		
H225	Highly flammable liquid and vapour.		
H226	Flammable liquid and vapour.		
H229	Pressurised container: May burst if heated.		
H280	Contains gas under pressure; may explode if heated.		
H312	Harmful in contact with skin.		
H315	Causes skin irritation.		

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Full text of H- and EUH-statements:			
H318	Causes serious eye damage.		
H319	Causes serious eye irritation.		
H332	Harmful if inhaled.		
H335	May cause respiratory irritation.		
H336	May cause drowsiness or dizziness.		
H351	Suspected of causing cancer.		
H400	Very toxic to aquatic life.		
H410	Very toxic to aquatic life with long lasting effects.		
H412	Harmful to aquatic life with long lasting effects.		
Press. Gas (Comp.)	Gases under pressure : Compressed gas		
Skin Irrit. 2	Skin corrosion/irritation, Category 2		
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis		

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:			
Aerosol 1	H222;H229 Expert judgement		
Skin Irrit. 2	H315	Calculation method	
Eye Irrit. 2	H319	Calculation method	
STOT SE 3	H336	Calculation method	
Aquatic Chronic 3	H412	Calculation method	

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.