

SPECTRAL PLAST 705 ADHESION INCREASING AGENT

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND THE COMPANY/UNDERTAKING

1.1. Product identifier

SPECTRAL PLAST 705 ADHESION INCREASING AGENT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Adhesion increasing agent. For professional use in car refinish.

1.3. Data of the supplier Safety Data Sheet

NOVOL Sp. z o.o.
Ul. Żabikowska 7/9
PL 62-052 Komorniki

Tel: +48 61 810-98-00
Fax: +48 61 810-98-09
www.novol.pl
novol@novol.pl
dokumentacja@novol.pl

Person responsible for the Safety Data Sheet

1.4. Emergency telephone number

+48 61 810-99-09 (from 7.00 to 15.00)

SECTION 2: HAZARD IDENTIFICATION

2.1. Classification of the substance or mixture

The mixture was classified as dangerous pursuant to current regulations - see section 15.

Classification 1272/2008/WE:

Reproductive Toxicity, category 2 (Repr. 2). Suspected of damaging the unborn child.

Specific target organ toxicity — Repeated exposure, Hazard Category 2 (STOT RE 2). May be fatal if swallowed and enters airways.

Specific target organ toxicity — Repeated exposure, Hazard Category 2 (STOT RE 2). May cause damage to organs through prolonged or repeated exposure.

Irritating effect on skin, category 2 (Skin Irrit. 2). Causes skin irritation.

Specific target organ toxicity — Single exposure, Hazard Category 3, Narcosis (STOT SE 3). May cause drowsiness or dizziness.

Liquid, flammable substances, category 2 (Flam. Liq. 2). Highly flammable liquid and vapour.

2.2. Label elements:

Contains:

Toluene

Pictograms:



Signal word:

Danger

H225

Highly flammable liquid and vapour.

H361d

Suspected of damaging the unborn child.

H304

May be fatal if swallowed and enters airways.

H373

May cause damage to organs through prolonged or repeated exposure.

H315

Causes skin irritation.

H336

May cause drowsiness or dizziness.

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260

Do not breathe vapours/spray.

P271

Use only outdoors or in a well-ventilated area.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

P301+310

IF SWALLOWED: Immediately call a doctor.

P331

Do NOT induce vomiting.

2.3. Other hazards

No available data.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable.

3.2. Mixtures

SPECTRAL PLAST 705 ADHESION INCREASING AGENT

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| | | | |
|-------------------------------|--|---|----------------------------|
| Product identification | | SPECTRAL PLAST 705 ADHESION INCREASING AGENT | |
| Substance name | Identification numbers | Classification and marking | Concentration [wt%] |
| Toluene | WE: 203-625-9 CAS: 108-88-3 Index no.: 601-021-00-3 Registration no.: 01-2119471310-51-XXXX | Flam. Liq. 2 H225 Repr. 2; H361d Asp. Tox. 1 STOT RE 2; H304; H373 Skin Irrit. 2; H315 STOT SE 3; H336 | 44-49 |
| Butyl acetate | EC: 204-658-1 CAS: 123-86-4 Index no.: 607-025-00-1 Registration no.: 01-2119485493-29-XXXX | Flam. Liq. 3; H226; STOT SE 3; H336 | 42-48 |

The full text of the hazard statements (H) is provided in Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information:
See section 11 of the Safety Data Sheet.

Inhalation:

Take the victim outside into fresh air, ensure quiet surrounding; in case of no breath, apply artificial respiration. Call a doctor.

Skin:

Take off contaminated clothing. Rinse contaminated skin with plenty of lukewarm water for about 15 minutes. If irritation persists, consult a doctor.

Eyes:

Rinse immediately with plenty of lukewarm water for about 15 minutes, avoid strong water jet-risk of cornea damage, consult a doctor.

Alimentary tract:

Do not provoke vomiting (choking risk). Rinse mouth with water. If conscious, administer 1-2 glasses of warm water. Call a doctor.

Person giving first aid should wear medical gloves.

4.2. Most important symptoms and effects, both acute and delayed

Harmful: danger of serious damage to health by prolonged exposure through inhalation. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

4.3. Indications of any immediate medical attention and special treatment needed

Special measures allowing for specialist and immediate aid should be available in the place of work.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Powder, foam resistant to alcohols, carbon dioxide, water mist.

5.2. Special hazards arising from the substance or mixture

Fire may cause generation of carbon dioxide and other toxic gases.

5.3. Advice for firefighters

Fire-fighting teams should wear self-contained breathing apparatus and light protective clothing. Cool adjacent tanks by spraying water at a safe distance.

SPECTRAL PLAST 705 ADHESION INCREASING AGENT

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

For persons not being the members of aid giving staff:

Eliminate sources of ignition. Ensure sufficient ventilation of the room. Avoid direct contact with the released substance. Avoid contact with skin and eyes. Personal protection measures - section 8 of the Safety Data Sheet.

For persons giving aid:

Persons giving aid should wear protective clothing made of coated, impregnated fabric, protective gloves (viton), tight protective glasses and breathing apparatus: gas mask with A type absorber.

6.2. Environmental precautions

Prevent leakage to the sewage system, surface waters, underground waters and soil.

6.3. Methods and materials for containment and cleaning up

Stop the leakage (close the liquid inflow, seal), place damaged container in an emergency container, remove the liquid mechanically and place it in an emergency container. In case of large leakage, embank the area. In case of small amounts, collect with the use of a binding agent (e.g. mica, diatomaceous earth, sand).

6.4. Reference to other sections

Personal protection measures - see section 8 of the Safety Data Sheet.

Disposal considerations - see section 13 of the Safety Data Sheet.

SECTION 7: HANDLING AND STORAGE OF THE SUBSTANCES AND MIXTURES

7.1. Precautions for safe handling

Keep away from heat and fire sources. Prevent leakage to the sewage system, surface waters, underground waters and soil. Use in well ventilated rooms. Do not smoke. Do not inhale fumes. Avoid contact with skin and eyes. Take precaution measures against electrostatic discharge. Use personal protection measures - section 8 of the Safety Data Sheet.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly sealed, original containers. Do not store near large amounts of organic peroxides and other strong oxidants. Take precaution measures against electrostatic discharge. Store in cool, well ventilated rooms. Protect from low temperatures, the influence of sunrays and heat sources.

7.3. Special end use(s)

For professional use in car refinish taking into consideration the information included in subsections 7.1 and 7.2.

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

8.1. Control parameters

Toluene CAS 108-88-3 according to:

- TRGS 900: MAK: 50ppm, MAK: 190 mg/m³, 4(II),DFG, H, Y
- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 50 ppm, 191 mg/m³, STEL 100ppm, 384 mg/m³, Sk

8.2. Exposure control

Respiratory tract protection:

Gas mask with A type absorber (EN 141).

Hand protection:

Protective gloves PN-EN 374-3 (viton, 0.7 mm thick, penetration time > 480 min, nitrile rubber, 0,4 mm thick, penetration time > 30 min)

Eye protection:

Tight protective glasses.

Skin protection:

Proper protective clothing (coated impregnated fabrics).

Workplace:

Fixed fume extraction and general ventilation.

Environmental exposure control:

Prevent leakage to the sewage system, surface waters, underground waters and soil.

SPECTRAL PLAST 705 ADHESION INCREASING AGENT

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

| | |
|-------------------------------------|---|
| Physical state | liquid |
| Colour | straw |
| Odour | strong, powerful |
| Odour threshold | 8 mg/m ³ (toluene) |
| pH | not applicable |
| Melting/freezing point | -95°C |
| Boiling point | 110 - 140°C |
| Flash point | 6°C |
| Autoignition point | about 270°C |
| Breakdown point | not specified |
| Evaporation rate | not specified |
| Flammability (solid, gas) | not applicable |
| Explosion limits | % bottom: 1.2 vol% top: 7.0 vol% (xylene) |
| Vapour pressure | 29 hPa (20°C) (toluene) |
| Vapour density (with regard to air) | 3.18 (toluene) |
| Density | about 0.9 g/cm ³ (20°C) |
| Solubility (in water) | poor |
| N-octanol/water division ratio | 2.85 (toluene) |
| Kinematic viscosity | 3 mm ² /s (40°C) |
| Explosive properties | not applicable |
| Oxidizing properties | not applicable |

9.2 Other informations

No available data.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

The product is not reactive under normal conditions.

10.2. Chemical stability

The product remains stable under normal conditions.

10.3. Possibility of hazardous reactions

Carbon monoxide and other toxic gases are generated as a result of thermal decomposition.

10.4. Conditions to be avoided

Highly flammable product. Avoid contact with strongly oxidizing agents, peroxides, strong acids and bases. Avoid generation and accumulation of static electricity. Protect from the influence of sunrays and heat sources.

10.5. Incompatible materials

Avoid contact with large amounts of organic peroxides, strong acids and bases as well as other strong oxidants.

10.6. Hazardous decomposition products

Carbon monoxide and other toxic gases are generated as a result of thermal decomposition.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

No experimental data available on the preparation. Evaluation was performed based on the data on dangerous ingredients included in the preparation.

a) Acute toxicity

| | | |
|---------|------------------------------------|-----------------------------|
| Toluene | LD ₅₀ (rat, oral) | 5000 mg/kg |
| | LC ₅₀ (rat, inhalation) | 15320 mg/m ³ /4h |

b) Skin corrosion/irritation

Causes skin irritation.

c) serious eye damage/irritation

No available data confirming the hazard class

d) respiratory or skin sensitisation

The mixture has not been classified as allergenic. No available data confirming the hazard class.

SPECTRAL PLAST 705 ADHESION INCREASING AGENT

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

e) germ cell mutagenicity

The mixture has not been classified as mutagenic. No available data confirming the hazard class.

f) carcinogenicity

The mixture has not been classified as cancerogenic. No available data confirming the hazard class.

g) reproductive toxicity

Suspected of damaging the unborn child.

h) STOT-single exposure

May cause drowsiness or dizziness

i) STOT- repeated exposure

May cause damage to organs through prolonged or repeated exposure.

j) aspiration hazard

May be fatal if swallowed and enters airways.

Exposure methods:

Inhalation: No data.

Skin: Causes skin irritation.

Eyes: May cause irritating effect.

If swallowed, May be fatal if swallowed and enters airways. The substance may cause irritation of the alimentary tract, nausea, vomiting and diarrhoea.

Poisoning symptoms:

Headache and vertigo, fatigue, decreased muscle power, drowsiness and, in exceptional instances, loss of consciousness.

SECTION 12: ECOLOGICAL INFORMATION

No experimental data available on the preparation. Evaluation was performed based on the data on dangerous ingredients included in the preparation.

12.1. Toxicity

Toluene

Daphnia magna /EC50 (48h) 11 mg/l

Acute toxicity for fish LC50 13mg/l/9h

Number in the catalogue of water hazardous substances: 194

Water hazard class: 2

12.2. Persistence and degradability

No available data.

12.3. Bioaccumulative potential

No available data.

12.4. Mobility in soil

Product very poorly soluble in water.

12.5. Results of PBT and vPvB assessment

No available data.

12.6. Other adverse effects

No available data.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

The product must be disposed of in compliance with proper local and statutory regulations with regard to waste - see point 15.

The product should be disposed with entities which are authorised to conduct activity in the area of collecting, recycling or utilization of waste.

Product remains:

Do not dispose the product into the sewage system. Do not store with communal waste. Remove the remains of the mixture carefully and leave to dry only in good ventilated rooms. The dried product is not harmful waste.

CAUTION: The remains should be dried in small portions. Keep them away from flammable products. High amounts of heat are released during chemical reaction!

Contaminated container:

A container containing unhardened remains of the product is harmful waste. Do not store with communal waste. The

SPECTRAL PLAST 705 ADHESION INCREASING AGENT

contaminated container should be disposed with entities which are authorized to collection, recover or disposal.

SECTION 14: TRANSPORT INFORMATION

| | ADR/RID | IMO/IMGD | IATA-DGR |
|---|---|----------|----------|
| 14.1. UN number | 1993 | 1993 | 1993 |
| 14.2. UN proper shipping name | FLAMMABLE LIQUID, N.O.S. (toluene) | | |
| 14.3. Transport hazard class(es) | 3 | 3 | 3 |
| 14.4. Packaging group | II | II | II |
| 14.5. Environmental hazards | none | none | none |
| 14.6. Special precautions for user | Do not transport together with materials of class 1 (excluding materials of class 1.4S) and some materials of classes 4.1 and 5.2. During transport, avoid direct contact with materials of classes 5.1 and 5.2. Do not use an open flame and do not smoke. | | |
| 14.7. Transport in bulk according to Annex II of MARPOL Convention and the IBC Code | Not applicable. | | |

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Regulation 2006/1907/WE
CLP - Regulation 1272/2008/WE

15.2. Chemical safety assessment

Not performed

SECTION 16: OTHER INFORMATION

Full text of the phrases identifying the types of hazards mentioned in sections 2-15

Flam.Liq.2/3 Liquid, flammable substances, category 2/3
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
Asp. Tox. 1 Aspiration hazard, Hazard Category 1
H304 May be fatal if swallowed and enters airways.
STOT RE 2 Specific target organ toxicity — Repeated exposure, Hazard Category 2
H373 May cause damage to organs through prolonged or repeated exposure.
Repr. 2 Reproductive Toxicity (category 2)
H361d Suspected of damaging fertility or the unborn child
STOT SE 3 Specific target organ toxicity— single exposure, category 3
H336 Might cause drowsiness or or dizziness.
Acute Tox. 4. Acute toxicity, category 4
H332 Harmful if inhaled.
H312 Harmful in contact with skin.
Skin Irrit. 2 Caustic/irritating effect on skin, category 2
H315 Causes skin irritation.
EUH66 Repeated exposure may cause skin dryness or cracking.

Explanation of the abbreviations and acronyms used in the Safety Data Sheet

CAS no – numerical symbol ascribed to a chemical substance by the American organization, Chemical Abstracts Service (CAS).

EC no. – a number ascribed to a chemical substance in the European List of Notified Chemical Substances (ELINCS) or a number in the European Inventory of Existing Chemical Substances mention in "No-longer polymers" publication (EINECS)

MPC – maximum permissible concentration of health hazardous substances in the work place

MPIC – maximum permissible instantaneous concentration

MPCC - maximum permissible ceiling concentration

PCB - permissible concentration in biological material

UN number - four-digit identification number of a substance, preparation or product pursuant to UN model regulations

ADR – European agreement on international road transport of hazardous materials

IMO – International Marine Organization

RID – Regulations for international rail transport of hazardous materials

IMDG-Code – International marine code for hazardous materials

SPECTRAL PLAST 705 ADHESION INCREASING AGENT

ICAO /IATA – Technical Instructions for Safe Air Transport of Hazardous Materials

SECTION 16: OTHER INFORMATION

The information contained herein is based on our current knowledge. This document shall not constitute a warranty of product characteristics.

Classification was made by calculation method according to the classification rules contained in Regulation 1272/2008/WE.

Other sources of data:

ECHA European Chemicals Agency

TOXNET Toxicology Data Network

IUCLID International Uniform Chemical Information Database

Changes: General update

Trainings:

With regard to handling, health and safety while working with hazardous substances and mixtures.

With regard to transport of hazardous goods pursuant to the requirements of ADR regulations.

Issued by: NOVOL Sp. z o.o.

Information available from: Research and Development Laboratory, tel. +48 61 810 99 09.