






Technical data sheet

## Spectral Prefill

- **PROPERTIES**

- semi-finished solvent-based aerosol product
- allowing for individual filling of a can containing propellant, solvent and additives facilitating application with a selected varnish
- allowing to match the colour to standard shades without using a spray gun
  - very easy application
  - non-irritating smell

| USE   |  |
|---|--|
| <ul style="list-style-type: none"> <li>• coloured acrylic topcoats</li> <li>• clearcoat</li> </ul>  |  |
| Not recommended for two-component products.   |  |
| CONTENT OF VOLATILE ORGANIC COMPOUNDS   |  |
| VOC II/B/a limit  | 850 g/l  |
| Actual VOC content  | <720 g/l   |
| USAGE INSTRUCTION   |  |
|  2min<br><br> 1-3 coats<br><br><br><br><br><br> 5s  | <p>One-component semi-finished product with propellant and special additives. Spectral Prefill can be filled with solvent-based varnish (400 ml can + 100 ml varnish).</p> <ul style="list-style-type: none"> <li>- Fill it with special machines for filling spray cans.</li> <li>- The product user is fully responsible for the final product.</li> <li>- Test the spray before use to check its colour and properties.</li> </ul> <p><b>CAUTION! Clean the valve after use. Turn the container upside down and spray for about 5 seconds until the valve is empty.</b></p> |
| STORAGE CONDITIONS  |  |
| <p>Store in a dry and cool room, away from sources of fire and heat.</p> <p>Avoid direct exposure to sunlight.</p>  |  |
| SHELF LIFE  |  |
| Spectral Prefill  | 5years/20°C  |
| SAFETY  |  |
| See Safety Data Sheet.  |  |
| OTHER INFORMATIONS  |  |
| <p>Registration number: 000024104.</p> <p>The effectiveness of our systems results from laboratory research and many years of experience. The data contained herein meets the current knowledge about our products and their application potential. We ensure high quality, provided the user follows the instructions and the work is performed in accordance with good workmanship. It is necessary to do a test application of the product due to its potentially different reaction with different materials. We may not be held liable for defects if the final result was affected by factors beyond our control.</p> |  |